

Reducers asymmetrical 500/200 to 630/600 MM

Popis

socket connection

PVC

#	d1 x d2	L	L1	L2	L3	X	s	s1
1	0500-0200	640	60	50	530	150	4,0	4,0
2	0500-0225	590	60	50	480	138	4,0	4,0
3	0500-0250	550	60	50	440	125	4,0	4,0
4	0500-0280	500	60	50	390	110	4,0	4,0
5	0500-0315	440	60	50	330	93	4,0	4,0
6	0500-0355	375	60	50	265	73	4,0	4,0
7	0500-0400	310	60	60	190	50	4,0	4,0
8	0500-0450	220	60	60	100	25	4,0	4,0
9	0560-0250	-	-	-	-	-	-	-
10	0560-0280	-	-	-	-	-	-	-
11	0560-0315	-	-	-	-	-	-	-
12	0560-0355	-	-	-	-	-	-	-
13	0560-0400	-	-	-	-	-	-	-
14	0560-0450	-	-	-	-	-	-	-
15	0560-0500	-	-	-	-	-	-	-
16	0600-0280	685	70	50	565	160	5,0	3,0
17	0600-0315	625	70	50	505	143	5,0	3,0
18	0600-0355	560	70	50	440	123	5,0	4,0
19	0600-0400	490	70	60	360	100	5,0	4,0
20	0600-0450	410	70	60	280	75	5,0	4,0
21	0600-0500	325	70	60	195	50	5,0	4,0
22	0600-0560	-	-	-	-	-	-	-
23	0630-0280	-	-	-	-	-	-	-
24	0630-0315	-	-	-	-	-	-	-
25	0630-0355	-	-	-	-	-	-	-
26	0630-0400	-	-	-	-	-	-	-
27	0630-0450	-	-	-	-	-	-	-
28	0630-0500	-	-	-	-	-	-	-
29	0630-0560	-	-	-	-	-	-	-

PPs

#	d1 x d2	L	L1	L2	L3	X	s	s1
1	0500-0200	650	60	50	540	150,0	6,0	3,0
2	0500-0225	605	60	50	495	137,5	6,0	3,5
3	0500-0250	565	60	50	455	125,0	6,0	3,5
4	0500-0280	510	60	50	400	110,0	6,0	4,0
5	0500-0315	445	60	50	335	92,5	6,0	5,0
6	0500-0355	385	60	50	275	72,5	6,0	5,0
7	0500-0400	320	60	60	200	50,0	6,0	6,0
8	0500-0450	225	60	60	105	25,0	6,0	6,0
9	0560-0250	705	90	50	565	155,0	6,0	3,5
10	0560-0280	645	90	50	505	140,0	6,0	4,0
11	0560-0315	585	90	50	445	122,5	6,0	5,0
12	0560-0355	525	90	50	385	102,5	6,0	5,0
13	0560-0400	455	90	60	305	80,0	6,0	6,0
14	0560-0450	365	90	60	215	55,0	6,0	6,0
15	0560-0500	280	90	60	130	30,0	6,0	6,0
16	0600-0280	-	-	-	-	-	-	-
17	0600-0315	-	-	-	-	-	-	-
18	0600-0355	-	-	-	-	-	-	-
19	0600-0400	-	-	-	-	-	-	-
20	0600-0450	-	-	-	-	-	-	-
21	0600-0500	-	-	-	-	-	-	-
22	0600-0560	-	-	-	-	-	-	-
23	0630-0280	765	90	50	625	175,0	6,0	4,0
24	0630-0315	705	90	50	565	157,5	6,0	5,0
25	0630-0355	645	90	50	505	137,5	6,0	5,0
26	0630-0400	575	90	60	425	115,0	6,0	6,0
27	0630-0450	480	90	60	330	90,0	6,0	6,0
28	0630-0500	400	90	60	250	65,0	6,0	6,0
29	0630-0560	325	90	90	145	35,0	6,0	6,0

PP

#	d1 x d2	L	L1	L2	L3	X	s	s1
1	0500-0200	650	60	50	540	150,0	6,0	3,0
2	0500-0225	605	60	50	495	137,5	6,0	3,5
3	0500-0250	565	60	50	455	125,0	6,0	3,5
4	0500-0280	510	60	50	400	110,0	6,0	4,0
5	0500-0315	445	60	50	335	92,5	6,0	5,0
6	0500-0355	385	60	50	275	72,5	6,0	5,0
7	0500-0400	320	60	60	200	50,0	6,0	6,0
8	0500-0450	225	60	60	105	25,0	6,0	6,0
9	0560-0250	705	90	50	565	155,0	6,0	3,5
10	0560-0280	645	90	50	505	140,0	6,0	4,0
11	0560-0315	585	90	50	445	122,5	6,0	5,0
12	0560-0355	525	90	50	385	102,5	6,0	5,0
13	0560-0400	455	90	60	305	80,0	6,0	6,0
14	0560-0450	365	90	60	215	55,0	6,0	6,0
15	0560-0500	280	90	60	130	30,0	6,0	6,0
16	0600-0280	-	-	-	-	-	-	-
17	0600-0315	-	-	-	-	-	-	-
18	0600-0355	-	-	-	-	-	-	-
19	0600-0400	-	-	-	-	-	-	-
20	0600-0450	-	-	-	-	-	-	-
21	0600-0500	-	-	-	-	-	-	-
22	0600-0560	-	-	-	-	-	-	-
23	0630-0280	765	90	50	625	175,0	6,0	4,0
24	0630-0315	705	90	50	565	157,5	6,0	5,0
25	0630-0355	645	90	50	505	137,5	6,0	5,0
26	0630-0400	575	90	60	425	115,0	6,0	6,0
27	0630-0450	480	90	60	330	90,0	6,0	6,0
28	0630-0500	400	90	60	250	65,0	6,0	6,0
29	0630-0560	325	90	90	145	35,0	6,0	6,0

PE

#	d1 x d2	L	L1	L2	L3	X	s	s1
1	0500-0200	650	60	50	540	150,0	6,0	3,0
2	0500-0225	605	60	50	495	137,5	6,0	3,5
3	0500-0250	565	60	50	455	125,0	6,0	3,5
4	0500-0280	510	60	50	400	110,0	6,0	4,0
5	0500-0315	445	60	50	335	92,5	6,0	5,0
6	0500-0355	385	60	50	275	72,5	6,0	5,0
7	0500-0400	320	60	60	200	50,0	6,0	6,0
8	0500-0450	225	60	60	105	25,0	6,0	6,0
9	0560-0250	705	90	50	565	155,0	6,0	3,5
10	0560-0280	645	90	50	505	140,0	6,0	4,0
11	0560-0315	585	90	50	445	122,5	6,0	5,0
12	0560-0355	525	90	50	385	102,5	6,0	5,0
13	0560-0400	455	90	60	305	80,0	6,0	6,0
14	0560-0450	365	90	60	215	55,0	6,0	6,0
15	0560-0500	280	90	60	130	30,0	6,0	6,0
16	0600-0280	-	-	-	-	-	-	-
17	0600-0315	-	-	-	-	-	-	-
18	0600-0355	-	-	-	-	-	-	-
19	0600-0400	-	-	-	-	-	-	-
20	0600-0450	-	-	-	-	-	-	-
21	0600-0500	-	-	-	-	-	-	-
22	0600-0560	-	-	-	-	-	-	-
23	0630-0280	765	90	50	625	175,0	6,0	4,0
24	0630-0315	705	90	50	565	157,5	6,0	5,0
25	0630-0355	645	90	50	505	137,5	6,0	5,0
26	0630-0400	575	90	60	425	115,0	6,0	6,0
27	0630-0450	480	90	60	330	90,0	6,0	6,0
28	0630-0500	400	90	60	250	65,0	6,0	6,0
29	0630-0560	325	90	90	145	35,0	6,0	6,0

PPs-el

#	d1 x d2	L	L1	L2	L3	X	s	s1
1	0500-0200	650	60	50	540	150,0	6,0	3,0
2	0500-0225	605	60	50	495	137,5	6,0	3,5
3	0500-0250	565	60	50	455	125,0	6,0	3,5
4	0500-0280	510	60	50	400	110,0	6,0	4,0
5	0500-0315	445	60	50	335	92,5	6,0	5,0
6	0500-0355	385	60	50	275	72,5	6,0	5,0
7	0500-0400	320	60	60	200	50,0	6,0	6,0
8	0500-0450	225	60	60	105	25,0	6,0	6,0
9	0560-0250	705	90	50	565	155,0	6,0	3,5
10	0560-0280	645	90	50	505	140,0	6,0	4,0
11	0560-0315	585	90	50	445	122,5	6,0	5,0
12	0560-0355	525	90	50	385	102,5	6,0	5,0
13	0560-0400	455	90	60	305	80,0	6,0	6,0
14	0560-0450	365	90	60	215	55,0	6,0	6,0
15	0560-0500	280	90	60	130	30,0	6,0	6,0
16	0600-0280	-	-	-	-	-	-	-
17	0600-0315	-	-	-	-	-	-	-
18	0600-0355	-	-	-	-	-	-	-
19	0600-0400	-	-	-	-	-	-	-
20	0600-0450	-	-	-	-	-	-	-
21	0600-0500	-	-	-	-	-	-	-
22	0600-0560	-	-	-	-	-	-	-
23	0630-0280	765	90	50	625	175,0	6,0	4,0
24	0630-0315	705	90	50	565	157,5	6,0	5,0
25	0630-0355	645	90	50	505	137,5	6,0	5,0
26	0630-0400	575	90	60	425	115,0	6,0	6,0
27	0630-0450	480	90	60	330	90,0	6,0	6,0
28	0630-0500	400	90	60	250	65,0	6,0	6,0
29	0630-0560	325	90	90	145	35,0	6,0	6,0

PVDF

#	d1 x d2	L	L1	L2	L3	X	s	s1
1	0500-0200	650	60	50	540	150,0	6,0	3,0
2	0500-0225	605	60	50	495	137,5	6,0	3,5
3	0500-0250	565	60	50	455	125,0	6,0	3,5
4	0500-0280	510	60	50	400	110,0	6,0	4,0
5	0500-0315	445	60	50	335	92,5	6,0	5,0
6	0500-0355	385	60	50	275	72,5	6,0	5,0
7	0500-0400	320	60	60	200	50,0	6,0	6,0
8	0500-0450	225	60	60	105	25,0	6,0	6,0
9	0560-0250	705	90	50	565	155,0	6,0	3,5
10	0560-0280	645	90	50	505	140,0	6,0	4,0
11	0560-0315	585	90	50	445	122,5	6,0	5,0
12	0560-0355	525	90	50	385	102,5	6,0	5,0
13	0560-0400	455	90	60	305	80,0	6,0	6,0
14	0560-0450	365	90	60	215	55,0	6,0	6,0
15	0560-0500	280	90	60	130	30,0	6,0	6,0
16	0600-0280	-	-	-	-	-	-	-
17	0600-0315	-	-	-	-	-	-	-
18	0600-0355	-	-	-	-	-	-	-
19	0600-0400	-	-	-	-	-	-	-
20	0600-0450	-	-	-	-	-	-	-
21	0600-0500	-	-	-	-	-	-	-
22	0600-0560	-	-	-	-	-	-	-
23	0630-0280	765	90	50	625	175,0	6,0	4,0
24	0630-0315	705	90	50	565	157,5	6,0	5,0
25	0630-0355	645	90	50	505	137,5	6,0	5,0
26	0630-0400	575	90	60	425	115,0	6,0	6,0
27	0630-0450	480	90	60	330	90,0	6,0	6,0
28	0630-0500	400	90	60	250	65,0	6,0	6,0
29	0630-0560	325	90	90	145	35,0	6,0	6,0

PVC-UV

#	d1 x d2	L	L1	L2	L3	X	s	s1
1	0500-0200	640	60	50	530	150	4,0	4,0
2	0500-0225	590	60	50	480	138	4,0	4,0
3	0500-0250	550	60	50	440	125	4,0	4,0
4	0500-0280	500	60	50	390	110	4,0	4,0
5	0500-0315	440	60	50	330	93	4,0	4,0
6	0500-0355	375	60	50	265	73	4,0	4,0
7	0500-0400	310	60	60	190	50	4,0	4,0
8	0500-0450	220	60	60	100	25	4,0	4,0
9	0560-0250	-	-	-	-	-	-	-
10	0560-0280	-	-	-	-	-	-	-
11	0560-0315	-	-	-	-	-	-	-
12	0560-0355	-	-	-	-	-	-	-
13	0560-0400	-	-	-	-	-	-	-
14	0560-0450	-	-	-	-	-	-	-
15	0560-0500	-	-	-	-	-	-	-
16	0600-0280	685	70	50	565	160	5,0	3,0
17	0600-0315	625	70	50	505	143	5,0	3,0
18	0600-0355	560	70	50	440	123	5,0	4,0
19	0600-0400	490	70	60	360	100	5,0	4,0
20	0600-0450	410	70	60	280	75	5,0	4,0
21	0600-0500	325	70	60	195	50	5,0	4,0
22	0600-0560	-	-	-	-	-	-	-
23	0630-0280	-	-	-	-	-	-	-
24	0630-0315	-	-	-	-	-	-	-
25	0630-0355	-	-	-	-	-	-	-
26	0630-0400	-	-	-	-	-	-	-
27	0630-0450	-	-	-	-	-	-	-
28	0630-0500	-	-	-	-	-	-	-
29	0630-0560	-	-	-	-	-	-	-

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.
Přeloženo z originálu výrobce.

Farprosys, s.r.o.
email: info@farprosys.com
tel. +420 728 757 770
www.atexventilatory.cz