

T-pieces 45° (socket connection)

Popis

socket connection

PVC

#	d	L	L1	L2	L3	H	s	kg
1	0050	170	35	100	25	75	3,0	0,2
2	0063	190	35	120	28	95	3,0	0,2
3	0075	215	40	135	30	105	3,0	0,3
4	0090	240	40	160	35	125	3,0	0,4
5	0110	290	40	210	50	160	3,0	0,6
6	0125	290	40	210	42	167	3,0	0,7
7	0140	325	45	235	48	188	3,0	0,8
8	0160	395	55	285	63	222	3,0	1,1
9	0180	420	50	320	70	250	3,0	1,4
10	0200	435	45	345	72	272	3,0	1,6
11	0225	490	50	390	82	307	3,5	2,3
12	0250	500	40	420	85	335	3,0	2,2
13	0280	570	50	470	95	375	4,0	3,7
14	0315	640	60	520	102	417	4,0	4,7
15	0355	675	50	575	110	465	4,0	5,6
16	0400	780	60	660	130	539	4,0	7,3
17	0450	925	65	795	172	622	5,0	12,2
18	0500	995	65	865	182	682	5,0	14,5
19	0560	-	-	-	-	-	-	-
20	0600	1155	65	1025	212	812	6,0	24,1
21	0630	-	-	-	-	-	-	-
22	0700	1340	80	1180	240	940	6,0	32,5
23	0710	-	-	-	-	-	-	-
24	0800	1520	100	1320	260	1060	6,3	44,3
25	0900	1685	100	1485	292	1192	7,0	61,2
26	1000	1850	100	1650	325	1325	8,0	85,2
27	1200	*	*	*	*	*	*	*
28	1250	2330	120	2090	420	1670	10,4	174,6

PPs

#	d	L	L1	L2	L3	H	s	kg
1	0050	170	35	100	25	75	3,0	0,1
2	0063	190	35	120	28	95	3,0	0,2
3	0075	215	40	135	30	105	3,0	0,2
4	0090	240	40	160	35	125	3,0	0,3
5	0110	290	40	210	50	160	3,0	0,4
6	0125	290	40	210	42	167	3,0	0,4
7	0140	325	45	235	48	188	3,0	0,6
8	0160	395	55	285	63	222	3,0	0,8
9	0180	420	50	320	70	250	3,0	0,9
10	0200	435	45	345	72	272	3,0	1,0
11	0225	490	50	390	82	307	3,5	1,5
12	0250	500	40	420	85	335	3,5	1,7
13	0280	570	50	470	95	375	4,0	2,5
14	0315	640	60	520	102	417	5,0	3,9
15	0355	675	50	575	110	465	5,0	4,6
16	0400	780	60	660	130	539	6,0	7,4
17	0450	925	65	795	172	622	6,0	9,8
18	0500	995	65	865	182	682	6,0	11,7
19	0560	1130	70	990	215	775	6,0	14,8
20	0600	-	-	-	-	-	-	-
21	0630	1250	70	1110	238	872	6,0	18,4
22	0700	-	-	-	-	-	-	-
23	0710	1415	80	1255	273	983	8,0	31,4
24	0800	1520	100	1320	260	1060	8,0	37,7
25	0900	1685	100	1485	292	1192	8,0	46,8
26	1000	1850	100	1650	325	1325	10,0	71,3
27	1200	*	*	*	*	*	*	*
28	1250	2330	120	2090	420	1670	10,0	112,3

PP

#	d	L	L1	L2	L3	H	s	kg
1	0050	170	35	100	25	75	3,0	0,1
2	0063	190	35	120	28	95	3,0	0,2
3	0075	215	40	135	30	105	3,0	0,2
4	0090	240	40	160	35	125	3,0	0,3
5	0110	290	40	210	50	160	3,0	0,4
6	0125	290	40	210	42	167	3,0	0,4
7	0140	325	45	235	48	188	3,0	0,6
8	0160	395	55	285	63	222	3,0	0,8
9	0180	420	50	320	70	250	3,0	0,9
10	0200	435	45	345	72	272	3,0	1,0
11	0225	490	50	390	82	307	3,5	1,5
12	0250	500	40	420	85	335	3,5	1,7
13	0280	570	50	470	95	375	4,0	2,5
14	0315	640	60	520	102	417	5,0	3,9
15	0355	675	50	575	110	465	5,0	4,6
16	0400	780	60	660	130	539	6,0	7,4
17	0450	925	65	795	172	622	6,0	9,8
18	0500	995	65	865	182	682	6,0	11,7
19	0560	1130	70	990	215	775	6,0	14,8
20	0600	-	-	-	-	-	-	-
21	0630	1250	70	1110	238	872	6,0	18,4
22	0700	-	-	-	-	-	-	-
23	0710	1415	80	1255	273	983	8,0	31,4
24	0800	1520	100	1320	260	1060	8,0	37,7
25	0900	1685	100	1485	292	1192	8,0	46,8
26	1000	1850	100	1650	325	1325	10,0	71,3
27	1200	*	*	*	*	*	*	*
28	1250	2330	120	2090	420	1670	10,0	112,3

PE

#	d	L	L1	L2	L3	H	s	kg
1	0050	170	35	100	25	75	3,0	0,1
2	0063	190	35	120	28	95	3,0	0,2
3	0075	215	40	135	30	105	3,0	0,2
4	0090	240	40	160	35	125	3,0	0,3
5	0110	290	40	210	50	160	3,0	0,4
6	0125	290	40	210	42	167	3,0	0,4
7	0140	325	45	235	48	188	3,0	0,6
8	0160	395	55	285	63	222	3,0	0,8
9	0180	420	50	320	70	250	3,0	0,9
10	0200	435	45	345	72	272	3,0	1,0
11	0225	490	50	390	82	307	3,5	1,5
12	0250	500	40	420	85	335	3,5	1,7
13	0280	570	50	470	95	375	4,0	2,5
14	0315	640	60	520	102	417	5,0	3,9
15	0355	675	50	575	110	465	5,0	4,6
16	0400	780	60	660	130	539	6,0	7,4
17	0450	925	65	795	172	622	6,0	9,8
18	0500	995	65	865	182	682	6,0	11,7
19	0560	1130	70	990	215	775	6,0	14,8
20	0600	-	-	-	-	-	-	-
21	0630	1250	70	1110	238	872	6,0	18,4
22	0700	-	-	-	-	-	-	-
23	0710	1415	80	1255	273	983	8,0	31,4
24	0800	1520	100	1320	260	1060	8,0	37,7
25	0900	1685	100	1485	292	1192	8,0	46,8
26	1000	1850	100	1650	325	1325	10,0	71,3
27	1200	*	*	*	*	*	*	*
28	1250	2330	120	2090	420	1670	10,0	112,3

PPs-el

#	d	L	L1	L2	L3	H	s	kg
1	0050	170	35	100	25	75	3,0	0,1
2	0063	190	35	120	28	95	3,0	0,2
3	0075	215	40	135	30	105	3,0	0,2
4	0090	240	40	160	35	125	3,0	0,3
5	0110	290	40	210	50	160	3,0	0,4
6	0125	290	40	210	42	167	3,0	0,4
7	0140	325	45	235	48	188	3,0	0,6
8	0160	395	55	285	63	222	3,0	0,8
9	0180	420	50	320	70	250	3,0	0,9
10	0200	435	45	345	72	272	3,0	1,0
11	0225	490	50	390	82	307	3,5	1,5
12	0250	500	40	420	85	335	3,5	1,7
13	0280	570	50	470	95	375	4,0	2,5
14	0315	640	60	520	102	417	5,0	3,9
15	0355	675	50	575	110	465	5,0	4,6
16	0400	780	60	660	130	539	6,0	7,4
17	0450	925	65	795	172	622	6,0	9,8
18	0500	995	65	865	182	682	6,0	11,7
19	0560	1130	70	990	215	775	6,0	14,8
20	0600	-	-	-	-	-	-	-
21	0630	1250	70	1110	238	872	6,0	18,4
22	0700	-	-	-	-	-	-	-
23	0710	1415	80	1255	273	983	8,0	31,4
24	0800	1520	100	1320	260	1060	8,0	37,7
25	0900	1685	100	1485	292	1192	8,0	46,8
26	1000	1850	100	1650	325	1325	10,0	71,3
27	1200	*	*	*	*	*	*	*
28	1250	2330	120	2090	420	1670	10,0	112,3

PVDF

#	d	L	L1	L2	L3	H	s	kg
1	0050	170	35	100	25	75	3,0	0,1
2	0063	190	35	120	28	95	3,0	0,2
3	0075	215	40	135	30	105	3,0	0,2
4	0090	240	40	160	35	125	3,0	0,3
5	0110	290	40	210	50	160	3,0	0,4
6	0125	290	40	210	42	167	3,0	0,4
7	0140	325	45	235	48	188	3,0	0,6
8	0160	395	55	285	63	222	3,0	0,8
9	0180	420	50	320	70	250	3,0	0,9
10	0200	435	45	345	72	272	3,0	1,0
11	0225	490	50	390	82	307	3,5	1,5
12	0250	500	40	420	85	335	3,5	1,7
13	0280	570	50	470	95	375	4,0	2,5
14	0315	640	60	520	102	417	5,0	3,9
15	0355	675	50	575	110	465	5,0	4,6
16	0400	780	60	660	130	539	6,0	7,4
17	0450	925	65	795	172	622	6,0	9,8
18	0500	995	65	865	182	682	6,0	11,7
19	0560	1130	70	990	215	775	6,0	14,8
20	0600	-	-	-	-	-	-	-
21	0630	1250	70	1110	238	872	6,0	18,4
22	0700	-	-	-	-	-	-	-
23	0710	1415	80	1255	273	983	8,0	31,4
24	0800	1520	100	1320	260	1060	8,0	37,7
25	0900	1685	100	1485	292	1192	8,0	46,8
26	1000	1850	100	1650	325	1325	10,0	71,3
27	1200	*	*	*	*	*	*	*
28	1250	2330	120	2090	420	1670	10,0	112,3

PVC-UV

#	d	L	L1	L2	L3	H	s	kg
1	0050	170	35	100	25	75	3,0	0,2
2	0063	190	35	120	28	95	3,0	0,2
3	0075	215	40	135	30	105	3,0	0,3
4	0090	240	40	160	35	125	3,0	0,4
5	0110	290	40	210	50	160	3,0	0,6
6	0125	290	40	210	42	167	3,0	0,7
7	0140	325	45	235	48	188	3,0	0,8
8	0160	395	55	285	63	222	3,0	1,1
9	0180	420	50	320	70	250	3,0	1,4
10	0200	435	45	345	72	272	3,0	1,6
11	0225	490	50	390	82	307	3,5	2,3
12	0250	500	40	420	85	335	3,0	2,2
13	0280	570	50	470	95	375	4,0	3,7
14	0315	640	60	520	102	417	4,0	4,7
15	0355	675	50	575	110	465	4,0	5,6
16	0400	780	60	660	130	539	4,0	7,3
17	0450	925	65	795	172	622	5,0	12,2
18	0500	995	65	865	182	682	5,0	14,5
19	0560	-	-	-	-	-	-	-
20	0600	1155	65	1025	212	812	6,0	24,1
21	0630	-	-	-	-	-	-	-
22	0700	1340	80	1180	240	940	6,0	32,5
23	0710	-	-	-	-	-	-	-
24	0800	1520	100	1320	260	1060	6,3	44,3
25	0900	1685	100	1485	292	1192	7,0	61,2
26	1000	1850	100	1650	325	1325	8,0	85,2
27	1200	*	*	*	*	*	*	*
28	1250	2330	120	2090	420	1670	10,4	174,6

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.
Přeloženo z originálu výrobce.

Farprosys, s.r.o.
email: info@farprosys.com
tel. +420 728 757 770
www.atexventilatory.cz