


## T-pieces with cleaning eyes



### Popis

to be installed on the premises with cover and o-ring gasket, without screws

## PVC

#	d x d1	L	L1	L2	s	H	d	B	k	d2	Anzahl d2
1	0110-0110	225	40	145	3,0	100	170	8	150	7	4
2	0125-0125	285	50	185	3,0	105	185	8	165	7	8
3	0140-0140	295	45	205	3,0	115	200	8	175	7	8
4	0160-0160	330	40	250	4,5	125	230	8	200	7	8
5	0180-0180	380	55	270	3,2	135	250	8	220	7	8
6	0200-0200	385	50	285	5,0	145	270	8	240	7	8
7	0225-0225	455	60	335	3,5	155	295	8	265	7	8
8	0250-0250	415	50	315	5,0	170	320	8	290	7	12
9	0280-0250	460	50	360	3,2	185	320	8	290	7	12
10	0315-0250	520	50	420	3,2	220	320	8	290	7	12
11	0355-0250	595	50	495	5,0	240	320	8	290	7	12
12	0400-0250	610	60	490	4,0	265	320	8	290	7	12

## PPs

#	d x d1	L	L1	L2	s	H	d	B	k	d2	Anzahl d2
1	0110-0110	225	40	145	3,0	155	170	8	150	7	4
2	0125-0125	285	50	185	3,0	165	185	8	165	7	8
3	0140-0140	295	45	205	3,0	170	200	8	175	7	8
4	0160-0160	330	40	250	3,0	180	230	8	200	7	8
5	0180-0180	380	55	270	3,0	190	250	8	220	7	8
6	0200-0200	385	50	285	3,0	200	270	8	240	7	8
7	0225-0225	455	60	335	3,0	215	295	8	265	7	8
8	0250-0250	415	50	315	3,5	225	320	8	290	7	12
9	0280-0250	460	50	360	3,5	240	320	8	290	7	12
10	0315-0250	520	50	420	3,5	220	320	8	290	7	12
11	0355-0250	595	50	495	3,5	240	320	8	290	7	12
12	0400-0250	610	60	490	3,5	265	320	8	290	7	12

## PP

#	d x d1	L	L1	L2	s	H	d	B	k	d2	Anzahl d2
1	0110-0110	225	40	145	3,0	155	170	8	150	7	4
2	0125-0125	285	50	185	3,0	165	185	8	165	7	8
3	0140-0140	295	45	205	3,0	170	200	8	175	7	8
4	0160-0160	330	40	250	3,0	180	230	8	200	7	8
5	0180-0180	380	55	270	3,0	190	250	8	220	7	8
6	0200-0200	385	50	285	3,0	200	270	8	240	7	8
7	0225-0225	455	60	335	3,0	215	295	8	265	7	8
8	0250-0250	415	50	315	3,5	225	320	8	290	7	12
9	0280-0250	460	50	360	3,5	240	320	8	290	7	12
10	0315-0250	520	50	420	3,5	220	320	8	290	7	12
11	0355-0250	595	50	495	3,5	240	320	8	290	7	12
12	0400-0250	610	60	490	3,5	265	320	8	290	7	12

## PE

#	d x d1	L	L1	L2	s	H	d	B	k	d2	Anzahl d2
1	0110-0110	225	40	145	3,0	155	170	8	150	7	4
2	0125-0125	285	50	185	3,0	165	185	8	165	7	8
3	0140-0140	295	45	205	3,0	170	200	8	175	7	8
4	0160-0160	330	40	250	3,0	180	230	8	200	7	8
5	0180-0180	380	55	270	3,0	190	250	8	220	7	8
6	0200-0200	385	50	285	3,0	200	270	8	240	7	8
7	0225-0225	455	60	335	3,0	215	295	8	265	7	8
8	0250-0250	415	50	315	3,5	225	320	8	290	7	12
9	0280-0250	460	50	360	3,5	240	320	8	290	7	12
10	0315-0250	520	50	420	3,5	220	320	8	290	7	12
11	0355-0250	595	50	495	3,5	240	320	8	290	7	12
12	0400-0250	610	60	490	3,5	265	320	8	290	7	12

## PPs-el

#	d x d1	L	L1	L2	s	H	d	B	k	d2	Anzahl d2
1	0110-0110	225	40	145	3,0	155	170	8	150	7	4
2	0125-0125	285	50	185	3,0	165	185	8	165	7	8
3	0140-0140	295	45	205	3,0	170	200	8	175	7	8
4	0160-0160	330	40	250	3,0	180	230	8	200	7	8
5	0180-0180	380	55	270	3,0	190	250	8	220	7	8
6	0200-0200	385	50	285	3,0	200	270	8	240	7	8
7	0225-0225	455	60	335	3,0	215	295	8	265	7	8
8	0250-0250	415	50	315	3,5	225	320	8	290	7	12
9	0280-0250	460	50	360	3,5	240	320	8	290	7	12
10	0315-0250	520	50	420	3,5	220	320	8	290	7	12
11	0355-0250	595	50	495	3,5	240	320	8	290	7	12
12	0400-0250	610	60	490	3,5	265	320	8	290	7	12

## PVDF

#	d x d1	L	L1	L2	s	H	d	B	k	d2	Anzahl d2
1	0110-0110	225	40	145	3,0	155	170	8	150	7	4
2	0125-0125	285	50	185	3,0	165	185	8	165	7	8
3	0140-0140	295	45	205	3,0	170	200	8	175	7	8
4	0160-0160	330	40	250	3,0	180	230	8	200	7	8
5	0180-0180	380	55	270	3,0	190	250	8	220	7	8
6	0200-0200	385	50	285	3,0	200	270	8	240	7	8
7	0225-0225	455	60	335	3,0	215	295	8	265	7	8
8	0250-0250	415	50	315	3,5	225	320	8	290	7	12
9	0280-0250	460	50	360	3,5	240	320	8	290	7	12
10	0315-0250	520	50	420	3,5	220	320	8	290	7	12
11	0355-0250	595	50	495	3,5	240	320	8	290	7	12
12	0400-0250	610	60	490	3,5	265	320	8	290	7	12

## PVC-UV

#	d x d1	L	L1	L2	s	H	d	B	k	d2	Anzahl d2
1	0110-0110	225	40	145	3,0	155	170	8	150	7	4
2	0125-0125	285	50	185	3,0	165	185	8	165	7	8
3	0140-0140	295	45	205	3,0	170	200	8	175	7	8
4	0160-0160	330	40	250	3,0	180	230	8	200	7	8
5	0180-0180	380	55	270	3,0	190	250	8	220	7	8
6	0200-0200	385	50	285	3,0	200	270	8	240	7	8
7	0225-0225	455	60	335	3,0	215	295	8	265	7	8
8	0250-0250	415	50	315	3,5	225	320	8	290	7	12
9	0280-0250	460	50	360	3,5	240	320	8	290	7	12
10	0315-0250	520	50	420	3,5	220	320	8	290	7	12
11	0355-0250	595	50	495	3,5	240	320	8	290	7	12
12	0400-0250	610	60	490	3,5	265	320	8	290	7	12

---

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.  
Přeloženo z originálu výrobce.

Farprosys, s.r.o.  
email: [info@farprosys.com](mailto:info@farprosys.com)  
tel. +420 728 757 770  
[www.atexventilatory.cz](http://www.atexventilatory.cz)