


## Double sockets



### Popis

Sockets/end caps

## PVC

#	d	L	L1	L2	s	kg
1	0050	80	25	30	3,0	0,1
2	0063	80	25	30	3,0	0,1
3	0075	100	35	30	3,0	0,2
4	0090	100	35	30	3,0	0,2
5	0110	100	40	20	3,0	0,1
6	0125	100	40	20	3,0	0,1
7	0140	100	40	20	3,0	0,1
8	0160	100	40	20	3,0	0,2
9	0180	100	40	20	3,0	0,2
10	0200	120	50	20	3,0	0,3
11	0225	120	50	20	3,0	0,4
12	0250	120	50	20	3,0	0,4
13	0280	120	50	20	3,0	0,4
14	0315	120	50	20	3,0	0,7
15	0355	130	50	30	4,0	0,7
16	0400	155	60	35	4,0	1,0
17	0450	160	60	40	4,0	1,4
18	0500	160	60	40	4,0	1,4
19	0560	-	-	-	-	-
20	0600	165	65	35	5,0	2,4
21	0630	-	-	-	-	-
22	0700	215	90	35	6,0	3,3
23	0710	-	-	-	-	-
24	0800	230	100	30	8,0	4,6
25	0900	250	100	50	8,0	6,8
26	1000	250	100	50	8,0	8,7
27	1200	*	*	*	*	*
28	1250	250	125	0	10,0	13,6
29	1400	350	175	0	10,0	21,3

## PPs

#	d	L	L1	L2	s	kg
1	0050	80	25	30	3,0	0,1
2	0063	80	25	30	3,0	0,1
3	0075	100	35	30	3,0	0,1
4	0090	100	35	30	3,0	0,1
5	0110	100	40	20	3,0	0,1
6	0125	100	40	20	3,0	0,1
7	0140	100	40	20	3,0	0,2
8	0160	100	40	20	3,0	0,2
9	0180	100	40	20	3,0	0,2
10	0200	120	50	20	3,0	0,2
11	0225	120	50	20	3,5	0,3
12	0250	120	50	20	3,5	0,4
13	0280	120	50	20	4,0	0,4
14	0315	120	50	20	5,0	0,8
15	0355	135	50	35	5,0	0,9
16	0400	155	60	35	6,0	1,0
17	0450	160	60	40	6,0	1,2
18	0500	160	60	40	6,0	1,0
19	0560	170	70	30	6,0	2,0
20	0600	-	-	-	-	-
21	0630	170	70	30	8,0	2,2
22	0700	-	-	-	-	-
23	0710	215	90	35	8,0	3,3
24	0800	230	100	30	8,0	4,2
25	0900	200	100	0	8,0	5,2
26	1000	200	100	0	8,0	7,2
27	1200	*	*	*	*	*
28	1250	250	125	0	10,0	9,0
29	1400	350	175	0	12,0	14,2

## PP

#	d	L	L1	L2	s	kg
1	0050	80	25	30	3,0	0,1
2	0063	80	25	30	3,0	0,1
3	0075	100	35	30	3,0	0,1
4	0090	100	35	30	3,0	0,1
5	0110	100	40	20	3,0	0,1
6	0125	100	40	20	3,0	0,1
7	0140	100	40	20	3,0	0,2
8	0160	100	40	20	3,0	0,2
9	0180	100	40	20	3,0	0,2
10	0200	120	50	20	3,0	0,2
11	0225	120	50	20	3,5	0,3
12	0250	120	50	20	3,5	0,4
13	0280	120	50	20	4,0	0,4
14	0315	120	50	20	5,0	0,8
15	0355	135	50	35	5,0	0,9
16	0400	155	60	35	6,0	1,0
17	0450	160	60	40	6,0	1,2
18	0500	160	60	40	6,0	1,0
19	0560	170	70	30	6,0	2,0
20	0600	-	-	-	-	-
21	0630	170	70	30	8,0	2,2
22	0700	-	-	-	-	-
23	0710	215	90	35	8,0	3,3
24	0800	230	100	30	8,0	4,2
25	0900	200	100	0	8,0	5,2
26	1000	200	100	0	8,0	7,2
27	1200	*	*	*	*	*
28	1250	250	125	0	10,0	9,0
29	1400	350	175	0	12,0	14,2

## PE

#	d	L	L1	L2	s	kg
1	0050	80	25	30	3,0	0,1
2	0063	80	25	30	3,0	0,1
3	0075	100	35	30	3,0	0,1
4	0090	100	35	30	3,0	0,1
5	0110	100	40	20	3,0	0,1
6	0125	100	40	20	3,0	0,1
7	0140	100	40	20	3,0	0,2
8	0160	100	40	20	3,0	0,2
9	0180	100	40	20	3,0	0,2
10	0200	120	50	20	3,0	0,2
11	0225	120	50	20	3,5	0,3
12	0250	120	50	20	3,5	0,4
13	0280	120	50	20	4,0	0,4
14	0315	120	50	20	5,0	0,8
15	0355	135	50	35	5,0	0,9
16	0400	155	60	35	6,0	1,0
17	0450	160	60	40	6,0	1,2
18	0500	160	60	40	6,0	1,0
19	0560	170	70	30	6,0	2,0
20	0600	-	-	-	-	-
21	0630	170	70	30	8,0	2,2
22	0700	-	-	-	-	-
23	0710	215	90	35	8,0	3,3
24	0800	230	100	30	8,0	4,2
25	0900	200	100	0	8,0	5,2
26	1000	200	100	0	8,0	7,2
27	1200	*	*	*	*	*
28	1250	250	125	0	10,0	9,0
29	1400	350	175	0	12,0	14,2

## PPS-EL

#	d	L	L1	L2	s	kg
1	0050	80	25	30	3,0	0,1
2	0063	80	25	30	3,0	0,1
3	0075	100	35	30	3,0	0,1
4	0090	100	35	30	3,0	0,1
5	0110	100	40	20	3,0	0,1
6	0125	100	40	20	3,0	0,1
7	0140	100	40	20	3,0	0,2
8	0160	100	40	20	3,0	0,2
9	0180	100	40	20	3,0	0,2
10	0200	120	50	20	3,0	0,2
11	0225	120	50	20	3,5	0,3
12	0250	120	50	20	3,5	0,4
13	0280	120	50	20	4,0	0,4
14	0315	120	50	20	5,0	0,8
15	0355	135	50	35	5,0	0,9
16	0400	155	60	35	6,0	1,0
17	0450	160	60	40	6,0	1,2
18	0500	160	60	40	6,0	1,0
19	0560	170	70	30	6,0	2,0
20	0600	-	-	-	-	-
21	0630	170	70	30	8,0	2,2
22	0700	-	-	-	-	-
23	0710	215	90	35	8,0	3,3
24	0800	230	100	30	8,0	4,2
25	0900	200	100	0	8,0	5,2
26	1000	200	100	0	8,0	7,2
27	1200	*	*	*	*	*
28	1250	250	125	0	10,0	9,0
29	1400	350	175	0	12,0	14,2

## PVDF

#	d	L	L1	L2	s	kg
1	0050	80	25	30	3,0	0,1
2	0063	80	25	30	3,0	0,1
3	0075	100	35	30	3,0	0,1
4	0090	100	35	30	3,0	0,1
5	0110	100	40	20	3,0	0,1
6	0125	100	40	20	3,0	0,1
7	0140	100	40	20	3,0	0,2
8	0160	100	40	20	3,0	0,2
9	0180	100	40	20	3,0	0,2
10	0200	120	50	20	3,0	0,2
11	0225	120	50	20	3,5	0,3
12	0250	120	50	20	3,5	0,4
13	0280	120	50	20	4,0	0,4
14	0315	120	50	20	5,0	0,8
15	0355	135	50	35	5,0	0,9
16	0400	155	60	35	6,0	1,0
17	0450	160	60	40	6,0	1,2
18	0500	160	60	40	6,0	1,0
19	0560	170	70	30	6,0	2,0
20	0600	-	-	-	-	-
21	0630	170	70	30	8,0	2,2
22	0700	-	-	-	-	-
23	0710	215	90	35	8,0	3,3
24	0800	230	100	30	8,0	4,2
25	0900	200	100	0	8,0	5,2
26	1000	200	100	0	8,0	7,2
27	1200	*	*	*	*	*
28	1250	250	125	0	10,0	9,0
29	1400	350	175	0	12,0	14,2

## PVC-UV

#	d	L	L1	L2	s	kg
1	0050	80	25	30	3,0	0,1
2	0063	80	25	30	3,0	0,1
3	0075	100	35	30	3,0	0,2
4	0090	100	35	30	3,0	0,2
5	0110	100	40	20	3,0	0,1
6	0125	100	40	20	3,0	0,1
7	0140	100	40	20	3,0	0,1
8	0160	100	40	20	3,0	0,2
9	0180	100	40	20	3,0	0,2
10	0200	120	50	20	3,0	0,3
11	0225	120	50	20	3,0	0,4
12	0250	120	50	20	3,0	0,4
13	0280	120	50	20	3,0	0,4
14	0315	120	50	20	3,0	0,7
15	0355	130	50	30	4,0	0,7
16	0400	155	60	35	4,0	1,0
17	0450	160	60	40	4,0	1,4
18	0500	160	60	40	4,0	1,4
19	0560	-	-	-	-	-
20	0600	165	65	35	5,0	2,4
21	0630	-	-	-	-	-
22	0700	215	90	35	6,0	3,3
23	0710	-	-	-	-	-
24	0800	230	100	30	8,0	4,6
25	0900	250	100	50	8,0	6,8
26	1000	250	100	50	8,0	8,7
27	1200	*	*	*	*	*
28	1250	250	125	0	10,0	13,6
29	1400	350	175	0	10,0	21,3

---

Technické údaje o produktech nejsou závazné. Konstrukční a rozměrové změny vyhrazeny.  
Přeloženo z originálu výrobce.

Farprosys, s.r.o.  
email: [info@farprosys.com](mailto:info@farprosys.com)  
tel. +420 728 757 770  
[www.atexventilatory.cz](http://www.atexventilatory.cz)